



8000™ Sealant

A Single Component Self-leveling Multipurpose Sealant/Adhesive

8000™ is designed specifically for RV and Mobile Home maintenance and repair. 8000™ exhibits excellent resistance to moisture, mildew and ozone.

Features

- Self-leveling
- Fast Skin Over
- UV Resistant
- Excellent Adhesion to Rubber

Seals and Bonds

EPDM, PVC, Wood, Asphalt, Aluminum and Galvanized Metal

Technical Data

Color	White, Aluminum and Translucent
Solvent	Aromatic Hydrocarbons
Weight	7.5 lbs. per Gallon
Solids Content	55%
Viscosity/Rheometer	27,000 – 30,000 cps @ 78°F [25.56°C] (Bookfield RTF)
Elongation	300%
Service Temperature	-40° to 250°F [-40° to 121°C]
Vapor Transmission	
VOC	300 g per Liter

Application

Temperature	Above 40°F [4°C]
Method	Trim Tip to Desired Bead Width and Apply to Clean, Dry Surfaces
Preparation	Clean and Dry Surface
Clean-up	Clean Tools with Mineral Spirits
Disposal	According to Local, State and Federal Laws

Storage

Temperature	Moderate Conditions
Shelf Life	1 Year



18466 Kenyon Ave. Lakeville, MN 55044 • 1.800.817.1827 • +1 952.898.3200 • Fax: +1 952.898.3232

info@permatite.com • www.permatite.com

© 2015 Permatite, A Division of DSI. All rights reserved. 10/2015

